

RRL Hose (Reinforced Rubber Lined Hose)

Non Percolating Flexible Delivery Hose

Conforming to IS : 636/1988 Type-A ISI Marked
 Application : This RRL Hose used for water delivery purpose in Fire-Fighting & Civil Engineering Applications etc.

Jacket : Circular woven jacket made from a special blend of cotton & synthetic yarn with high abrasion and heat resistance Jacket is also treated with suitable rot proofing agent.

Reinforcement : A thin fabric reinforcement bonded by a Special adhesive.

Rubber Lining: A rubber inner lining with suitable rubber compound which gives flexibility, durability & better resistance.

Standard Length: 7.5 Mtrs, 15 Mtrs, 22.5 Mtrs & 30 Mtrs.

End Connection: As per customer requirements

FEATURES

Compact, Flexible & Light weight, Abrasion Resistant, Ability to withstand high operating & back Pressure.



IS : 636 : 1988 Type-A



CML No. 2595168

DIAMETER MM	BURSTING PRESSURE KCF/CM	TEST PROOF PRESSURE KGF/CM	COIL DIAMETER (30MTR) CM
38	35.7	21.4	44-45
50	35.7	21.4	44-45
63	35.7	21.4	44-45
70	35.7	21.4	44-45

Xtra Coat RRL Hose (Reinforced Rubber Lined Hose)

Non Percolating Flexible Delivery Hose

TECHNICAL SPECIFICATIONS

Hose : RRL Hose with Elastomeric Coating conforming to As per IS : 636/1988 Type-A

Application : This RRL Hose is used for water delivery purpose in Fire Fighting, Oil & Power Sector, Industrial Plants, & Sailing Vessels.

Jacket : Circular Woven jacket made Form a 100% synthetic yarn with high abrasion and heat resistance. The woven jacket is treated with a special Elastomeric. Coating to give protection against moisture and fungus.

Reinforcement : A thin fabric Reinforcement bonded by a Special Adhesive.

Rubber Lining: A rubber inner lining with suitable rubber compound which gives flexibility, durability & better resistance.

Standard Length: 7.5 Mtrs, 15 Mtrs, 22.5 Mtrs & 30 Mtrs.

End Connection: As per customer requirements

FEATURES

Compact, Flexible & Light weight , Abrasion, Bacteria & fungus Resistant Ability to withstand high operating & back pressure , Unaffected with mild dew.



CE - 9208

DIAMETER MM	BURSTING PRESSURE KCF/CM	TEST PROOF PRESSURE KGF/CM	COIL DIAMETER (30MTR) CM
38	35.7	21.4	44-45
50	35.7	21.4	44-45
63	35.7	21.4	44-45
70	35.7	21.4	44-45