



## Swinging Type Wall Mounted First Aid Hose Reel Drum

### TECHNICAL SPECIFICATION

Conforming to: IS:884/ 1958



CE - 9208

IS : 884 : 1985



CML No. 8700004412

Size: Inlet : 1" Threaded Inlet Connection

Type : Swinging 180° Wall Mounting

Outlet : 3/4" / 1" / 1-1/2 outlet connection For House to accommodate 30/ 36/ 40 Mtrs. Hoses

### Performance Test

Hydrostatic Test : Tested at 21 Kgf/cm<sup>2</sup>

Range & Water Flow rate test at 7Kgf/ cm<sup>2</sup>

(A) Discharge: 24 LPM

(B) Range (Jet Length) : 6 Mtr (Min)

Halogram:- Sticker Stuck on Wheel



Hub Sides & Wall Bracket	M.S. Sheet of IS : 513
Swivel Joint	LTB - 2 of IS : 318
Pipe with Fitting	Steel of IS : 1239 Part 1
Nozzle	IS : 8090
Hose Reel Tubing	Thermoplastic Hose confirming to IS : 12585

## Thermoplastic Hose Pipe ( Textile Reinforced ) for Water

### TECHNICAL SPECIFICATION

IS: 12585 - Type - 1 W.P. 6 Kgf/cm<sup>2</sup>

IS: 12585 - Type - 2 W.P. 10 Kgf/cm<sup>2</sup>



CE - 9208

IS : 12585 : 1988



CML No. 8700001313

### Construction:-

Lining : A flexible Thermoplastic Lining, Smooth in bore.

Reinforcement : A Natural or Synthetic Textile

Reinforcement : A flexible thermoplastics cover, which may have a smooth or fluted.

Nominal Bore (ID) : 10.00 mm to 50.00 mm

Application: This Hose is used for water delivery & Fire Fighting purpose.

